

1. PROPRIETARY PRODUCT/MANUFACTURER

- 1.1. **Proprietary Product:** Resilient Adapter Mouldings, Americans with Disabilities Act compliant (ADA). Made in USA.
- 1.2. **Manufacturer:**
Tarkett North America Phone: (800) 899-8916
30000 Aurora Rd. (440) 543-8916
Solon, Ohio 44139
Web: www.tarkettna.com
- 1.3. **Proprietary Product Description:**
- 1.3.1. **Construction:** Tarkett Adaptors are manufactured from a homogeneous composition of polyvinyl chloride (PVC), high quality additives, and colorants. Tarkett transition are designed for interior applications only.
- 1.3.2. **Styles:**
- CTA-XX-A:** 1/4" (6.35mm) carpet to 1/8" (3.18mm) resilient materials, 1-3/8" (3.49cm) cap with 1/8" (3.18mm) wide support
- CTA-XX-C:** 1/4" (6.35mm) carpet to 1/8" (3.18mm) resilient materials, 1" (2.54cm) cap with 3/32" (3.18mm) wide support
- CTA-XX-D:** 5/16" (7.94mm) carpet to 1/16" (1.57mm) to 1/8" (3.18mm) resilient materials, 1-5/8" (4.13cm) cap with 7/16" (6.35mm) wide support, Anti-rock design for roller traffic
- CCA-XX:** 5/16" (7.94mm) carpet to 3/8" (9.53mm) ceramic tile, 1" (2.54cm) cap with 3/8" (9.53mm) wide support
- CWA-XX:** 5/16" (7.94mm) carpet to 1/2" (12.7mm) wood flooring, 1" (2.54cm) cap with 3/8" (9.53mm) wide support

1.3.3. **Physical Characteristics:**

Length: 12 ft (3.66m)

Packaging: 20 pcs/carton for CTA-XX-A & CTA-XX-C
10 pcs/carton for CTA-XX-D, CCA-XX, & CWA-XX

2. PRODUCT PERFORMANCE AND TECHNICAL DATA

- 2.1. **Slip Resistance (ASTM D 2047):** ≥ .5 SCOF
- 2.2. **Fire Resistance:** ASTM E 648/NFPA 253 (Critical Radiant Flux) - Class 1

3. INSTALLATION

- 3.1. See Tarkett Resilient Moulding installation and maintenance instructions for complete details.
- 3.2. **Adhesives:**
Tarkett 946 Premium Contact Adhesive (Non-porous surfaces)
Application: Brush on T-moulding and track on mitered corner areas
Approximate coverage:
1 Quart (0.95 liters) – 24 to 36 sq. ft.
1 Gallon (3.79 liters) – 100 to 150 sq. ft.

4. AVAILABILITY AND COST

Available through authorized Tarkett distributors nationwide.

5. WARRANTY

Limited 2 year warranty. For complete details, contact Tarkett or an authorized Tarkett distributor.

6. MAINTENANCE

72 hours after installation is completed, initial maintenance procedures must be implemented in accordance with manufacturer's requirements. Refer to Tarkett Resilient Moulding Installation & Maintenance Instructions for complete maintenance details.

7. TECHNICAL SERVICES

Samples: Submittal samples for verification and approval available upon request from Tarkett. Samples shall be submitted in compliance with the requirements of the contract documents. Accepted and approved samples shall constitute the standard materials which represent materials installed on the project.

For current Installation and Maintenance Instructions, Product Specifications, and other technical data, visit us on the web at www.tarkettna.com or contact Tarkett at 1-800-899-8916.