



The beauty of better engineering.

ProGen[™] is a radical leap forward in flooring technology a rigid core construction engineered from the inside, out designed to outperform the rigors of daily wear. It holds up beautifully to the demands of busy, active households - from kids and pets to water and dirt. ProGen also handles sunlight and extreme temperature changes, resisting buckling, denting and warping.

With beautiful, authentic-looking designs, an easy, no-mess installation, and guaranteed long-term wear, ProGen promises a better experience every step of the way.













No Temperature Limits

Thermal Stability

Use in any room in the home. ProGen is designed to handle wide temperature fluctuations from windows and sunlight.

Easy Installation

Its easy Uniclic® system is faster than traditional installation systems, saving you time and money.

Durable

Resists the stresses of modern life from children to high heels to heavy furniture.

Waterproof

Safe to use in kitchens and bathrooms for a modern look throughout the home.

Rigid Core

Overcomes subfloor imperfections, unlike traditional luxury vinyl tile.

IIC rating of 68 means superior sound absorption to drastically improve overall comfort.

From Tarkett, a Global Leader in Flooring for Over 100 Years

ProGen's next-generation technology is designed to stand up to the demands of modern life—and whatever is thrown, dropped, spilled or scraped on it. Because ProGen is durable, waterproof, dimensionally stable, and easy to install, it can be used in any room—including all-season rooms with extreme temperature changes and rooms that are most prone to moisture and spills, like kitchens and baths.











Floating Floor	Quick and Simple Angle-Angle Click
Above/At/ Below Grade	✓
No Acclimation	✓
3-Seasons Roor	n 🗸
No Temperature Limitations	· 🗸
Acoustic Rating	Total IIC of 68 (6" Concrete Slab + Suspended Ceiling)

New, Trend-Setting Designs

Make your design visions a reality through a variety of on-trend designs.













Dimensional Stability and Durability



Contraction and Expansion in Mils (ASTM F2199)



Residual Indentation (ASTM F1914 0.178" @ 140 lbs.)



Durham Pine | Sun-Toned 270264014



Rock Maple | Medio 270264012



Stained Maple | Carmine 270264015



Cerused Oak | Powder 270265013



Tannin Walnut | Gris 270265016



Aurora Oak | Starry Night 270265020



Red Oak | Ginger 270264016



Durham Pine | Tavern 270264013



Vista Oak | Limed Natural 270265015



Stokes Range | Relic 270265018



Cerused Oak | Denim 270265014



Brushed Pine | Sorrel 270265019



Stokes Range | Dusk 270265017



West Oak | Drift 270266024



Spicebark Hickory | Fumed 270266016



Spicebark Hickory | Comino 270266017



North Shore Pine | Cascade 270266020



Milled Oak | Copper 270266018



West Oak | Loft 270266022



West Oak | Natural 270266021



Pacific Madrone | Natural 270266019



West Oak | Mountane 270266023

Matching Accessories are Available

Flexible transitions create a safe and effective passage from one flooring surface to another. Available in all coordinating designs, these important accessories standout by blending in.






A Selection of Stone Patterns.



Fleury Travertine | Verona 270288000



Villa Slate | Spire 270288001



Arcadian | Featherstone 270288002



Pavestone | Luxor 270288003



Pavestone | Cambria 270288004



Outland Path | Brindle 270282009



Marble Nouveau | Ibis 270282006



Quartzite | Dune 270282007



Quartzite | Ashen 270282008





SPECIFICATIONS							
Total Thickness	5 mm						
ProGen Core [™] Technology	4 mm						
Acoustical Backing Layer	1 mm IXPE						
Wear Layer Thickness	20 mils						
Material	Phthalate Free, 100% Virgin Material						
Reusable Content	100% Reclaimable						
Plank Size	5" x 48"	7" x 48"	7" x 60"	9" x 24"	12" x 24"		
Sq. Ft. per Carton	26.68 sq. ft.	28.52 sq. ft.	29.61 sq. ft.	20.96 sq. ft.	28.03 sq. ft.		
Planks per Carton	16	12	10	14	14		
Cartons per Pallet	56	50	40	64	54		
Lbs. per Carton	42 lbs.	44 lbs.	45 lbs.	33.5 lbs.	45 lbs.		
ASTM F2199 (Dimensional Stability)	Passes						
ASTM F1914 (Residual Indentation)	Passes (PSI Equivalent > 5,000 lbs.)						
ASTM F1514 (Heat Stability)	Passes						
ASTM F1515 (Light Stability)	Passes						
ASTM E2179 (Impact Sound Reductions)	Δ IIC \geq 20 dB						
IIC Impact Sound Reduction Rating	68						
ASTM F925 (Resistance to Chemicals)	Passes						
ASTM D5116 (VOC Requirements)	Passes < 0.1 mg/m ³						
Scratch/Scuff/Abrasion Properties	Excellent						
Phillips Castor Chair @ 100 lbs.	Passes @ 25,000 cycles						
Installation System	Uniclic®						
Certification	FloorScore® Certification						
Residential Warranty	Lifetime						
Light Commercial Warranty	15-Year						
3-Seasons Warranty	10-Year						



Tarkett North America

30000 Aurora Road Solon, OH 44139 USA: 1-877-TARKETT (1-877-827-5388) Canada: 1-877-436-6267

PAVESTONE | CAMBRIA | 270288004

ON THE FRONT COVER: