

Moxie™

FIBERFLOOR® PRO SERIES

Beautiful
and healthy
for those
you love
most.™



INDENTATION



QUIET



CLEANS EASILY



FAMILY FRIENDLY



PET FRIENDLY



WATER RESISTANT



Barn Jazz | Buffed | 24151

 **Tarkett**

Tarkett FiberFloor® – Moxie™



24001 | Norway Modular
Grey
48" x 48",
38.5" Drop, DNR



24011 | Wendel Oak
Gunstock
36" x 36",
18" Drop, DNR



24012 | Wendel Oak
Grey
36" x 36",
18" Drop, DNR



24101 | Travertine
Grey Matters
48" x 72", DNR



24111 | Mix
Talc
36" x 36",
18" Drop, DNR



24121 | Colorado Stone
Grey
36" x 36",
18" Drop, DNR



24131 | Pompeii
Latte
36" x 48",
12" Drop, DNR



24141 | Remix
Old Barn
48" x 72", DNR



24151 | Barn Jazz
Buffed
36" x 72",
18" Drop, DNR



24161 | Roca
White Polar
36" x 72", DNR



According to a recent survey*, respondents identified the following conditions as having the most impact on their household:



66%
pollen allergy



49%
asthma



40%
mold allergy



39%
dust mites



78%

of respondents said they are more likely to buy a product if it has an independent third-party certification from a nonprofit organization like AAFA.



What is asthma & allergy friendly* certification?

The **asthma & allergy friendly*** certification is a regulated, physician-led certification that accounts for the total installation (product and adhesive) and the ability of a product to be cleaned to minimize the number of allergens released into the environment. This certification helps to set a new standard, and offers consumers a guide for selecting flooring products based on their likelihood to create an allergic or asthmatic reaction.

The top benefits of using CERTIFIED asthma & allergy friendly* products

63% said the products/services reduce their, or their family's exposure to allergy triggers.

53% reported that the products/services improve air quality in their home.

47% believe the products/services are better for their health.

Specifications	
Series	24XXX
Nominal Total Thickness	0.125" (3.2 mm)
Wear Layer Thickness	0.012" (0.31 mm)
Wear Layer Finish	Urethane (Low Gloss)
Width	12" (3.6m)
Maximum Roll Size	104 sq. yd. (86.9 m ²)
Weight per Sq. Yd.	3.82 lbs (1.7 kg)
ASTM F1303	Type I, Grade 3, Class C
ASTM D2047 (Slip)	>.5
ASTM E648 (Fire)	>.45 W/cm ²
ASTM E662 (Smoke)	<450
ASTM F137 (Flexibility)	1/4" (6.4mm)
ASTM F925 (Staining)	Excellent
ASTM F970 Static Load Limit	75 lbs./sq. in. (5.3 kg/cm ²)
ASTM F1514 (Heat Stability)	Δ E < 8
ASTM F1515 (Light Stability)	Δ E < 8
ASTM E2179 (Impact Sound Reductions)	Δ IIC 25 dB
Installation System	Glueless or full-spread (Multi-Family Applications)
Location	Below, on and above grade concrete, above grade plywood
Adhesive	Tarkett® QBond-One® or 959
Seam Sealer	Tarkett DT-65 Seam Sealer
HUD/FHA Minimum/HUD	Yes, ≥/0.010" wear layer
FloorScore® Certification	SCS-EC10.3-2014: SCS-FS-02746
Phthalate Free	Yes
CERTIFIED asthma & allergy friendly* by the Asthma and Allergy Foundation of America (AAFA) & Asthma Society of Canada	AAFC: 1155/11/05/01/2066

* METHODOLOGY: AAFA and Research Now conducted an online survey of adults at least 18 years of age who are a current U.S. resident (n=1844) from August 23 and September 12, 2018 to better understand patient and consumer awareness, perceptions and values of certified products and the **asthma & allergy friendly*** Certification Program, as well as buyer behaviors and demands.

TOTAL sample size (n=1844) • Public Survey (representative sample) 1005; AAFA Survey (AAFA constituents) 839

The CERTIFIED ASTHMA & ALLERGY FRIENDLY Mark is a Registered Certification Mark of the ASTHMA AND ALLERGY FOUNDATION OF AMERICA AND ALLERGY STANDARDS LTD.



Visit tarkettna.com for complete warranty details.

Tarkett North America

30000 Aurora Road
Solon, OH 44139
USA: 1-877-TARKETT (1-877-827-5388)
Canada: 1-877-436-6267

www.tarkettna.com

Connect with us.



For more accurate color representation, we suggest you visit an authorized Tarkett dealer to view an actual product sample.

©2020 Tarkett North America 12/2020