Starters[™]

FIBERFLOOR® PRO SERIES

Beautiful and healthy for those you love most.[™]













FAMILY FRIENDLY PET FRIENDLY WATER RESISTANT



Quartzite | Quarry | FE141

Tarkett

Tarkett FiberFloor® - Starters™



FE033 | Mojave Slate Taupe 36" x 48" 12" Drop, DNR



FE051 | Rustic Oak 14.4" Drop, DNR



FE052 | Rustic Oak Harbour Brown 14.4" Drop, DNR



FE101 | Casa Grande 12" Drop, DNR



FE111 | Somerset Hickory Natural 36" x 48" 12" Drop, DNR



36" x 72", DNR



FE121 | American Chestnut FE131 | Alamo Stone Raw Earth 36" x 36", DNR



FE141 | Quartzite Quarry 36" x 48" 16" Drop, DNR



FE151 | Mossa Stone Stormy Greys 36" x 24". 18" Drop, DNR



FE161 | Urban Vintage 48" x 144", DNR



FE171 | Coppertino Shady 36" x 18", 18" Drop, DNR



FE181 | Rhythm 36" x 36", 18" Drop, DNR



FE191 | Golden Lightning 12" Drop, DNR



FE201 | Continental* 36" x 36", DNR

According to a recent survey*, respondents identified the following conditions as having the most impact on their household:



66% pollen allergy



49% asthma



39% dust mites



of respondents said they are more likely to buy a product if it has an independent third-party certification from a nonprofit organization like AAFA.



What is asthma & allergy friendly certification?

The asthma & allergy friendly certification is a regulated, physician-led certification that accounts for the total installation (product and adhesive) and the ability of a product to be cleaned to minimize the number of allergens released into the environment. This certification helps to set a new standard, and offers consumers a guide for selecting flooring products based on their likelihood to create an allergic or asthmatic reaction.

The top benefits of using CERTIFIED asthma & allergy friendly products

63%

said the products/services reduce their, or their family's exposure to allergy triggers.

reported that the products/services improve air quality in their home.

47%

believe the products/services are better for their health.

Specifications	
Series	FEXXX
Nominal Total Thickness	0.68° (1.73 mm)
Wear Layer Thickness	0.012" (0.31 mm)
Wear Layer Finish	Urethane (Low Gloss)
Width	12' (3.6m)
Maximum Roll Size	164 sq. yd. (137 m²)
Weight per Sq. Yd.	2.73 lbs (1.24 kg)
ASTM F1303	Type I, Grade 3, Class C
ASTM D2047 (Slip)	>.5
ASTM E648 (Fire)	>.45 W/cm²
ASTM E662 (Smoke)	<450
ASTM F137 (Flexibility)	1/4" (6,4mm)
ASTM F925 (Staining)	Excellent
ASTM F970 Static Load Limit	75 lbs./sq. in. (5.3 kg/cm²)
ASTM F1514 (Heat Stability)	ΔΕ<8
ASTM F1515 (Light Stability)	ΔE<8
ASTM E2179 (Impact Sound Reductions)	Δ IIC 21 dB
Installation System	Glueless or full-spread (Multi-Family Applications)
Location	Below, on and above grade concrete, above grade plywood
Adhesive	Tarkett® QBond-One" or 959
Seam Sealer	Tarkett DT-65 Seam Sealer
HUD/FHA Minimum/HUD	Yes, =/>0.010" wear layer
FloorScore® Certification	SCS-EC10.3-2014: SCS-FS-02746
Phthalate Free	Yes
CERTIFIED asthma & allergy friendly * by the Asthma and Allergy Foundation of America (AAFA) & Asthma Society of Canada	AAFC: 1155/11/05/01/2066

^{*} METHODOLOGY: AAFA and Research Now conducted an online survey of adults at least 18 years of age who are a current U.S. resident (n=1844) from August 23 and September 12, 2018 to better understand patient and consumer awareness, perceptions and values of certified products and the asthma & allergy friendly® Certification Program, as well as buyer behaviors and demands.



the ASTHMA AND ALLERGY FOUNDATION OF AMERICA and ALLERGY STANDARDS LTD.

warranty details



Tarkett North America

30000 Aurora Road Solon, OH 44139 USA: 1-877-TARKETT (1-877-827-5388) Canada: 1-877-436-6267





