

1. PROPRIETARY PRODUCT/MANUFACTURER

1.1 **Proprietary Product:** Affordable water resistant, glue down luxury vinyl flooring. Suitable for Residential and Light Commercial environments.

1.2 **Manufacturer:**

Tarkett North America Phone: (800) 899-8916
30000 Aurora Rd. (440) 543-8916
Solon, Ohio 44139
Web: www.tarkett.com

1.3 **Proprietary Product Description:**

1.3.1 **Construction:** Luxury vinyl made from phthalate free, virgin raw materials.

1.3.2 **Characteristics:**

- **Edge Treatment:** Square
- **Wear Layer:** .012" (0.3mm)
- **Nominal Thickness:** 0.80" (2 mm)
- **Gloss:** Matte

1.3.3 **Plank Size & Packaging**

- **Width:** 6" (152.4 mm)
- **Length:** 48" (1219.2 mm)
- **Planks per Carton:** 18
- **Square Feet per Carton:** 36 (3.34 m²)
- **Weight per Carton:** 27.56 lbs (12.50 kg)
- **Cartons per Pallet:** 78

2. PRODUCT DETAILS AND TECHNICAL DATA

2.1 **Dimensional Stability:** ASTM F2199: Passes

2.2 **Flammability:**

- **Fire Performance:** ASTM E648 $\geq .45$ W/cm²: Class 1
- **Smoke Density:** ASTM E662 ≤ 450 optical density

2.3 **Light Stability:** ASTM F515 $\Delta E \leq 8$

2.4 **Heat Stability:** ASTM F1514 $\Delta E \leq 8$

2.5 **Stain Resistance:** ASTM F925: Passes

2.6 **Slip Resistance:** ASTM D2047: SCOF ≥ 0.5

2.7 **Static Load Limit:** ASTM F970: Passes

2.8 **FloorScore® Certification:** SCS-EC10.3-2014 v4.0

3. INSTALLATION

See FreeSpan installation instructions found at www.tarkett.com for complete details.

3.1 **Adhesive:**

- **Tarkett Qbond One**
Releasable - Medium Nap Roller
Permanent - 1/32" x 1/16" x 1/32" trowel
- **Tarkett 959 Vinyl Tile and Plank Adhesive**
Permanent - Porous: 1x16 x 1/16 x 1/16 V-notch
Non Porous: 1/32 x 1/16 x 1/32 U-notch
Porous / Non Porous: Medium nap roller

4. AVAILABILITY AND COST

Available through authorized Tarkett Retailers.

5. MAINTENANCE

See Residential Maintenance instructions found at www.tarkett.com for complete details.

6. TECHNICAL SERVICES

Visit us on the web at www.tarkett.com

Contact Technical Support at (888) 639 8275, or E-mail Resilient.TechnicalSupport@tarkett.com

7. WARRANTY

- 25 YEAR LIMITED RESIDENTIAL WARRANTY
- 7 YEAR LIMITED LIGHT COMMERCIAL WARRANTY



Tarkett North America

Technical Services Department
30000 Aurora Road
Solon, Ohio 44139
888-639-8275

Resilient.TechnicalSupport@tarkett.com

www.tarkett.com

