

Choose Your Color

InStudio™ offers an array of visuals, from classic hardwood grains to sophisticated stones. All you have to do is pick your favorite. You'll find the same captivating designs with InStudio™ in both a 12 mil and 20 mil wear layer option, making it easier than ever to seamlessly meet diverse performance requirements.

Choose Your Wearlayer

Choose **InStudio™ 12** for installations with light to moderate foot traffic. Choose **InStudio™ 20** for higher traffic areas as it offers enhanced resistance to wear and tear.















InStudio™ LUXURY VINYL FLOORING



Ironsides InStudio™ 12: **IN211-12** InStudio™ 20: **IN211-20**



White Oak InStudio™ 12: **IN212-12** InStudio™ 20: **IN212-20**



Classic Oak InStudio™ 12: **IN221-12** InStudio™ 20: **IN221-20**



Brown InStudio™ 12: **IN222-12** InStudio™ 20: **IN222-20**



Vintage Oak InStudio™ 12: **IN231-12** InStudio™ 20: **IN231-20**



Castle Oak Newbury InStudio™ 12: **IN241-12** InStudio™ 20: **IN241-20**



Castle Oak InStudio™ 12: **IN242-12** InStudio™ 20: **IN242-20**



Castle Oak InStudio™ 12: **IN243-12** InStudio™ 20: **IN243-20**



Cooper Bay Copper InStudio™ 12: **IN251-12** InStudio™ 20: **IN251-20**



Lodge Plank Grey Pearl InStudio™ 12: **IN261-12** InStudio™ 20: **IN261-20**



Toscana Golden Isle InStudio™ 12: **IN301-12** InStudio™ 20: **IN301-20**



Concreto Onyx InStudio™ 12: **IN311-12** InStudio™ 20: **IN311-20**




Moody Vibes InStudio™ 20: **IN321-20**



Quiet Luxury InStudio™ 20: **IN322-20**



Sahara Dune InStudio™ 12: **IN271-12** InStudio™ 20: **IN271-20**



Nova Greystone InStudio™ 12: **IN281-12** InStudio™ 20: **IN281-20**



Pacifica Bianco InStudio™ 12: **IN291-12** InStudio™ 20: **IN291-20**

SPECIFICATIONS						
Finish	Durable Urethane					
Edge	Square					
Flammability	ASTM E648 ≥ .45 W/cm ² ASTM E662 ≤ 450 optical density					
Resistance to Light	ASTM F1515 ΔE ≤ 8					
Resistance to Heat	ASTM F1514 ΔE ≤ 8					
Resistance to Chemicals	ASTM F925 Passes					
Certification	FloorScore® Certified					
Installation Method	Adhesive					

InStudio™ 12: 12 MIL WEAR LAYER | 2.0 MM THICKNESS

Format	Finished Size (Nominal)	Pieces per Carton	Weight per Carton	Area per Carton	Cartons per Pallet	Warranty
Plank	6" x 48" (152.4 mm x 1219.2 mm)	18	26 lbs. (12 kg)	36 sq. ft. (3.345 m²)	78	25-Year Residential
Tile	18" x 18" (457.2 mm x 457.2 mm)	16	26 lbs. (12 kg)	36 sq. ft. (3.345 m²)	76	Limited 7-Year
THE	12" x 24" (304.8 mm x 609.6 mm)	18	26 lbs. (12 kg)	36 sq. ft. (3.345 m²)	78	Light Commercial Limited

InStudio™ 20: 20 MIL WEAR LAYER | 2.5 MM THICKNESS

Format	Finished Size (Nominal)	Pieces per Carton	Weight per Carton	Area per Carton	Cartons per Pallet	Warranty
Plank	6" x 48" (152.4 mm x 1219.2 mm)	22	39 lbs. (18 kg)	44 sq. ft. (4.088 m²)	60	30-Year Residential
Tile	18" x 18" (457.2 mm x 457.2 mm)	18	36 lbs. (16 kg)	40.5 sq. ft. (3.763 m²)	56	Limited 10-Year Light Commercial Limited
Tile	12" x 24" (304.8 mm x 609.6 mm)	22	39 lbs. (18 kg)	44 sq. ft. (4.088 m²)	54	

Tarkett North America

www.TarkettHome.com

















