

ProGen Plus™ Rigid Core Luxury Vinyl Flooring

Product Specification

1. PROPRIETARY PRODUCT/MANUFACTURER

- 1.1 **Proprietary Product:** Waterproof, floating luxury vinyl flooring. Suitable for Residential, Light Commercial, and 3-Season type environments.
- 1.2 **Manufacturer:**
Tarkett North America Phone: (888) 639-8275
30000 Aurora Rd.
Solon, Ohio 44139
Web: www.tarketthome.com
- 1.3 **Proprietary Product Description:**
- 1.3.1 **Construction:** Rigid core, floating luxury vinyl made with a plastic core and attached acoustical backing.
- 1.3.2 **Characteristics:**
- **Locking Mechanism:** Angle-Angle
 - **Edge Treatment:** Micro Bevel
 - **Nominal Thickness:** 0.236" (6 mm)
 - **Wear Layer:** .020" (0.5 mm)
 - **Core Thickness:** 0.197" (5 mm)
 - **Acoustical Backing:** 0.039" (1 mm) IXPE

1.3.3 Plank Size & Packaging

Nominal Plank Size	7"x60" (181 x 1544 mm)	9"x60" (230 x 1552 mm)
Planks per Carton	8	6
SQFT per Carton	24.11 (2.24 m ²)	23.03 (2.14 m ²)
Weight per Carton	49.99 lbs. (22.67 kg)	49.92 lbs. (22.64 kg)
Cartons per Pallet	45	48

2. PRODUCT DETAILS AND TECHNICAL DATA

- 2.1 **Rigid Polymeric Core Specifications:** ASTM F3261 Class 1, Type A or B, Grade 1, Backing Class B
- 2.2 **Dimensional Stability:** ASTM F2199: Passes
- 2.3 **Light Stability:** ASTM F515 $\Delta\Sigma \leq 8$
- 2.4 **Heat Stability:** ASTM F1514 $\Delta\Sigma \leq 8$
- 2.5 **Residual Indentation:** ASTM F1914: Passes
- 2.6 **Stain Resistance:** ASTM F925: Passes
- 2.7 **Slip Resistance:** ASTM D2047: SCOF ≥ 0.5
- 2.8 **Impact Sound:** ASTM E2179: $\Delta IIC \geq 23$
- 2.9 **Impact Insulation Class:** ASTM E492: (6" concrete) IIC 53
- 2.10 **FloorScore® Certification:** SCS-FS-09863
- 2.11 **Assure Certified™:** SCS-AC-09930

3. INSTALLATION

See ProGen installation instructions found at www.tarketthome.com for complete details.

4. AVAILABILITY AND COST

Available through authorized Tarkett Retailers.

5. MAINTENANCE

See Residential Maintenance instructions found at www.tarketthome.com for complete details.

6. TECHNICAL SERVICES

Visit us on the web at www.tarketthome.com

Contact Technical Support at (888) 639 8275, or E-mail Resilient.TechnicalSupport@tarkett.com

7. WARRANTY

- LIFETIME YEAR LIMITED RESIDENTIAL WARRANTY
- 15 YEAR LIMITED LIGHT COMMERCIAL WARRANTY
- 10 YEAR 3 SEASONS ROOM LIMITED WARRANTY



Tarkett North America

Technical Services Department
30000 Aurora Road
Solon, Ohio 44139
888-639-8275

Resilient.TechnicalSupport@tarkett.com

www.tarketthome.com

